

MOTIF COLOURS

Substance g/m ²	80	120	160
Caliper µm (approx)	107	160	219
Smoothness (Bendtsen) ml/min TS	250	250	250
Smoothness (Bendtsen) ml/min WS	250	250	250
Rigidity (Taber Stiffness Units) 15° MD	2.5	6.3	24
Rigidity (Taber Stiffness Units) 15° CD	1.1	3.6	8.4
Surface pH	8.2	8.2	8.2

Technical Capability

Copier Guaranteed	Yes, mono
Laser Guaranteed	Yes, mono and colour
Inkjet Guaranteed	Yes, mono and colour
Plain Paper Fax	80g/m ² only
Toy Safety	Yes, complies with EN71 Part 3 Toy Safety Regulations
Permanence of Paper	Yes, meets with ISO9706 requirements for Permanence of Paper

Environmental Information

Fibre Source	Virgin wood fibre from South Africa, Austria, Sweden, Portugal, Spain and Chile.
Bleaching	Pulp is bleached using an Elemental Chlorine Free (ECF) process
Disposal	This material can be disposed of by recycling and incineration for energy recovery
Accreditation	Produced at a mill that is certified to the ISO14001 environmental management standard FSC Certified where advised, please contact local Sales Office for more information.