

XE (HI-TACK) SELF-ADHESIVE WATERPROOF LASER FILM (KRAFT BACKING)

Matt aqueous coated polyester film, with a permanent pressure sensitive adhesive laminated to a 95gsm kraftpaper release liner. The construction is optimised for dry toner print applications.

Property Characteristics:

Property	Typical Value	Unit	Test Method
Total Thickness	170 +/- 6	μ	Electronic Micrometer
Weight	190 +/- 6	g/m ²	Internal Method
Face Film Thickness (no adhesive)	60 +/- 2	μ	Electronic Micrometer
Liner Thickness	93 +/- 4	μ	Electronic Micrometer
Gloss 60	<4	%	BYK Gardner
Opacity	>96	%	TAPPI T519
Tensile Strength (Face)	MD 14 TD 15	KgF/mm ²	ASTM D882-83
Melting Point	250	C	ASTM E794-85
Adhesive Peel on Stainless Steel	>12	N/25mm	FINAT 1 (30min dwell)
Adhesive Application Temperature	+5 to +50	C	Internal Method
Adhesive Service Temperature	+0 to +50	C	Internal Method

Compatibility:

Suitable for most dry toner (laser/LED) & thermal transfer print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Applications and characteristics:

- Tear resistant, high stability, water resistant front face.
- Ideal for signage and rugged labelling.
- Matt surface promotes toner adhesion and smoothest imaging on a wide range of toner based printers.
- High grab, high-tack permanent acrylic pressure sensitive adhesive for long duration.
- 95gsm coated paper release.

Recommended conditions for use: 10C -30C, 40% -55% RH
for storage: 10C -20C, 20% -55% RH

Please return unused product to its original packaging

Shelf Life:

18 months after delivery (under recommended storage conditions)