

4CC SMOOTH UNCOATED

4CC Smooth Uncoated has an extremely smooth surface and outstanding formation and it produces superior print quality and guarantees exceptionally sharp, well-defined images and text. Colours appear true to the original with fantastic clarity.

4CC Smooth Uncoated has been made whiter moving from a CIE whiteness of 150 to 160. The whiter shade enhances the print contrast and gives better lift to the images. In addition the surface of the heavier substances has been made smoother to enable more even colour reproduction especially in solid areas of print.

New 4CC Smooth Uncoated is packed in film wrappers that look great with a stunning gloss appearance that shows off the updated design of 4CC.

4CC's multi functionality ensures optimum results on any number of machines and printing processes, such as colour copying, colour laser, mono and colour inkjet, black and white, high-resolution imaging and lithographic preprint. High quality consistency guarantees reliable machine performance.

Ageing resistance:

4CC has filing feasibility according to standard ISO 9706 and DIN 6738.

Technical Specifications

Parameters (gsm)	Standard	90	100	120	160	200	220	250	280	300
Caliper	-	100	113	125	157	196	215	245	275	300
Smoothness (Bendtsen)	ISO 8791	40	40	40	40	40	40	40	40	40
Whiteness CIE	ISO 11475	160	160	160	160	160	160	160	160	160
Opacity %	ISO 2471	93	95	97	98	98	99	99	99.5	99.5